

BONESCHI ARMOURED VEHICLES

The tradition







The tradition





furgoni blindati
''SAFEBANK''
armoured security vans



The tradition















M 40.13 WM/P



Armoured vehicle, ordinary 7.62 NATO ballistic level on IVECO chassis 40.13 WM 4x4. Crew of seven (plus driver) and/or armament up to a payload of 800 Kg.

This vehicle can be used as a personal carrier for patrol and quick intervention operations, etc. It is transportable by boat, railway (international profile), air (C130) or road.



M 40.13 WM/P









M 40.13 WM/P

Dimensions (mm : ±3% tolerance)

Wheelbase	2800
Front track	1670
Rear track	1670
Front overhang	1050
Rear overhang	900
Overall length	5050
Overall width	2100
Overall height	2300
Approch angle (degr.)	40
Departure angle (degr.)	40
Ground clearance (rear axle)	266

Weights (kg; $\pm 3\%$ tolerance)

G.V.W. max allowed
Front axle rating
Rear axle rating
Curb (with spare wheel,75Kg driver)
Front
Rear
Payload
Towability

Performance

Gradeability	over 60%
Side slope	over 30%
Fording depth	0.7 m
Turning radius (wb. 2800 mm)	6 m
Top speed	over 100 Km/h







"Carabinieri" version









"Anti Riot" version

- Certified root plate
- Public order devices, including emergency light, acoustic warning, speaker and searching light
- Smokebombs









"Tropicalized" version

- Powered airconditioning system
- Powered insulation
- Snorkel
- Adjustable front grid









"Cívil Protection" version

Particularly equipped for Civil protection organization, this vehicle combines sanitary and rescue equipments







"International" versions











